

Authorised Dealer



VEMC

VIJAY ENGINEERING AND MACHINERY CO.

100 1920
2020

KIRLOSKAR BROTHERS LTD.



Enriching Lives



KOSM
THREE PHASE
OPEN-WELL PUMPS



KIRLOSKAR BROTHERS LIMITED

A Kirloskar Group Company

Established 1888

KIRLOSKAR PUMPS

TECHNICAL SPECIFICATION

Head Range	: Upto 38 metres
Discharge Range	: Upto 11 lps
Power Ratings	: 0.37 to 1.5 kW (0.5 to 2 HP)
Voltage Range	: 300 to 440 Volts (Three Phase)
Insulation	: B Class
Protection	: IP 68

MATERIAL OF CONSTRUCTION

Impeller	: Cast Iron / Noryl
Delivery Casing	: Cast Iron
Motor Body	: Cast Iron
Shaft	: Stainless Steel

APPLICATIONS

- Domestic and community water supply
- Gardening and small farm irrigation
- Water fountains
- Construction site
- Water supply to over head tanks

FEATURES

Wide Voltage Design

The motor is designed to withstand wide voltage fluctuations from 350 to 440 volts and reduces motor burning in case of low voltage.

Lightweight And Compact Design

Constructed with special grade engineering materials, compact designs for ease of handling and installation.

Dynamically Balanced Rotating Parts

Minimum vibrations protect components from damages during the operations, thus ensuring consistent performance as concentricity is maintained.

Replaceable Wearing Parts

All wearing parts within the pumps are easily accessible and replaceable which facilitates ease of maintenance thereby extending the life of the pump.

Easy Maintainable Designs

Easy maintainable design and better interchangeability of components so that the pump can be serviced even at remote locations by semi-skilled technicians.

CED – Cathodic Electro Deposition

CED is the latest coating technology for corrosion resistance with uniform coating. It provides 5 times more protection over conventional painting, resulting in longer life. All major CI parts of Kirloskar pumps coming in contact with the water are CED coated.

High Efficiency And Energy Saving Design

Innovative design manufactured at state-of-the-art plant, delivers optimum efficiency at lower energy consumption resulting in significant cost savings.

Advanced Water Cooled Motors Designs

The motor is filled with potable water which protects it from overheating and facilitates smoother and trouble free operation for years.

PERFORMANCE CHART FOR 'KOS-M' SERIES, 2 POLE, OPENWELL SUBMERSIBLE PUMPS, AT RATED VOLTAGE, 50 Hz FREQUENCY, THREE PHASE A.C. POWER SUPPLY

Sr. No.	Pump Model	Power Rating		Pipe Size (mm)		Rated Voltage (Volts)	TOTAL HEAD IN METRES													
		kW	HP	SUC.	DEL.		8	10	12	14	16	18	20	22	24	26	28	30	32	34
							DISCHARGE IN LITERS PER SECOND													
1	KOS-0516M	0.37	0.5	25	25	415	1.7	1.6	1.5	1.3	0.9	0.4	-	-	-	-	-	-	-	-
2	KOS-116M	0.75	1.02	50	40	415	4.8	4.4	3.9	3.1	1.9	-	-	-	-	-	-	-	-	-
3	KOS-123M	0.75	1.02	32	25	415	4.8	4.6	4.2	3.8	3.5	3	2.4	1.6	-	-	-	-	-	-
4	KOS-128M	0.75	1.02	25	25	415	-	-	1.9	1.8	1.8	1.7	1.5	1.2	0.6	-	-	-	-	-
5	KOS-134M	0.75	1.02	25	25	415	-	-	1.9	1.8	1.8	1.7	1.6	1.5	1.4	1.3	1.1	0.9	0.6	0.2
6	KOS-1.522M	1.1	1.5	50	40	415	6.1	5.8	5.3	4.8	4.3	3.6	2.5	-	-	-	-	-	-	-
7	KOS-1.525M	1.1	1.5	50	40	415	-	-	-	-	3.4	3.2	2.9	2.6	2.4	2.1	1.7	1	-	-
8	KOS-216M	1.5	2	65	50	415	11	9.9	8.7	7	-	-	-	-	-	-	-	-	-	-
9	KOS-225M	1.5	2	50	40	415	-	-	4.8	4.6	4.4	4.2	3.7	3.2	2.5	-	-	-	-	-
10	KOS-235M	1.5	2	50	40	380	-	-	4.4	4.2	4	3.8	3.5	3.2	2.9	2.5	2	1.4	0.2	-
							12	14	16	18	20	22	24	26	28	30	32	34	36	38
11	KOS-1.540M	1.1	1.5	32	25	415	-	-	-	-	-	-	1.9	1.8	1.6	1.4	1.3	1.1	0.9	0.6

Note : All models are also available in single phase. expect KOS-235M
Performance applicable to liquid of specific gravity 1 and Viscosity as of water.

Authorised Dealer

VIJAY ENGINEERING AND MACHINERY COMPANY

1420 C, Laxmipuri, Kolhapur, Pincode - 416002, Maharashtra.

Tel : (0231) 2642515, 2641877, Mobile no : 9923207988/87/89, Email Id: sales@vemc.in